

**DESCRIPTION**

The **Micro-Sub 6** is a high definition subwoofer designed for permanent installation. It uses a 6" low frequency driver in a very compact sealed enclosure.

Working in conjunction with external DSP processing, it achieves maximum bass output from a minimum enclosure size. DSP options include an Innovox proprietary powered system processor, or DSP configurations from our free library for Biamp, BSS and Symetrix processors.

The **Micro-Sub 6** complements the Innovox *Slim Line Series* of shallow profile surface-mount loudspeakers and the *Flex-Video Series* of display-mounted loudspeakers. It also is used as a low-bass component in extended range distributed audio systems.



*(shown without grille)*

**KEY FEATURES:**

- ultra compact profile
- excellent transient response
- 45 Hz low frequency extension
- minimal 4.1-inch depth

**APPLICATIONS:**

- theme venues and restaurants
- boardrooms
- video presentation / program audio
- retail spaces

**NOMINAL DATA**

Frequency Response	45 – 350 Hz ± 3 dB
Impedance	8 Ω
Power Handling	175W long term program (AES-2)
Maximum Output	102 dB long term; 108 dB peak
Dimensions	height: 10.13" / 257 mm width: 14.13" / 359 mm depth: 4.10" / 104 mm
Net Weight	10.5 lbs / 4.8 kg
Shipping Weight	12 lbs / 5.5 kg

**DESCRIPTIVE DATA**

System Configuration	Dedicated Low frequency
Components & Loading	(1) 6" LF driver, sealed
Recommended High-Pass Filter	4 <sup>th</sup> order Butterworth @ 40 Hz
Cabinet Type	Rectangular, sealed
Enclosure Material	Hardwood multi-ply plywood
Finish	Black or White (custom colors available)
Connectors	Dual binding head screws
Suspension Hardware	steel yoke
Grille	Powder-coated perforated steel standard

**DIMENSIONAL DRAWINGS**

