



AMERICAN LOUDSPEAKER INNOVATION

Slim Line Series –

SL-2.1RH

DESCRIPTION

The **SL-2.1RH** is a horizontal-mount version of the SL-2.1R. This slim profile 2-way loudspeaker is designed to be surface-mounted and disappear into the architectural surroundings. Its precision ribbon HF driver and two 4" long-excursion LF drivers resolve complex audio program with detail and clarity that does not seem possible from such a small package.



The addition of an available SBC-110 ceiling mounted sub-woofer extends low frequency response to 34 Hz and increases maximum system SPL.

KEY FEATURES:

- slim profile (only 2" deep by 4" wide)
- 120° H x 90° V coverage
- employs precision ribbon HF driver
- blends into architectural environment
- easily integrated into architectural casework with optional millwork adapter kit

NOMINAL DATA

Frequency Response	120 – 20,000 Hz ± 3 dB
Sensitivity	92 dB @ 2.83 volts / 1M
Impedance	6Ω
Power Handling	90 W long term program
Maximum Output	108 dB long term / 114 dB peak @ 1 meter
Nominal Coverage Angles	120° H x 90° V
Dimensions	height: 4.56 " / 116 mm width: 18.00 " / 457 mm depth: 2.06 " / 52 mm
Net Weight	7.0 lbs / 3.2 kg
Shipping Weight	8.0 lbs / 3.6 kg



(cross-section)

APPLICATIONS:

- sound for video presentation
- home theater center channel
- under-balcony fill
- stair-riser fill (with adapter kit)
- choir-rail foldback / fill

DESCRIPTIVE DATA

System Configuration	Low profile 2-way
Components & Loading	(2) 4" long-excursion LF drivers, (1) 3" ribbon HF driver
High-Pass Filter	Built-in 1 st order @ 120 Hz
Enclosure Type	Sealed enclosure, very low profile
Enclosure Material	Steel chassis with composite endcaps
Finish	Black or White (custom colors available)
Connectors	Dual binding head screws
Suspension Hardware	Mounting brackets included
Grille	Integral, fabric wrapped

296 North Pascal Street
Saint Paul MN 55104

innovoxaudio.com
PROUDLY MADE IN THE U.S.A.